



®

## SL438E

电脑高速直驱套结机

Computerized Direct Drive Bar-tacking Sewing Machine



## SL5

自动送扣装置

Auto Feed Button Machine

新款  
NEW

## SL438E

产品特点 Function &amp; Specification:

适用各种产品工序  
Suitable for various product processes低张力缝制技术  
Low tension sewing technology自动剪线  
Automatic thread trimming生产效率高  
High productivity

产品规格 Specification	SL438E
线迹形式 Stitch Type	单针平缝 single needle lockstitch
最高缝纫速度 Max. Speed	2700 rpm
缝纫尺寸X/Z Sewing Size	最大6.4x6.4mm Max. 6.4x6.4mm
送布驱动方式 Feed Drive Mode	Y-0 间歇送布（脉冲马达驱动） Intermittent feeding (pulse motor drive)
针距 Stitch distance	0.5~12.7mm
最大针数 Max. Number Of Stitches	210,000针(包括可加的210,000针) Includes addable 210,000 stitch
压脚高度 Presser Foot Height	最大13mm Max. 13mm
旋梭 Hook	标准半转旋梭(双倍旋梭选配) Standard half-turn hook (double hook optional)
缝纫纽扣尺寸 Sewing button size	纽扣外径8-30mm(选配20-30mm纽扣夹) Button outer diameter 8-30mm (Optional 20-30mm button clip)
马达 Motor	AC 伺服马达 550W AC servo motor 550W
电源 Power Supply	单相 Single-phase 100V/220V, 三相 Three-phase 200V/380V/400V

## SL5

产品特点 Function &amp; Specification:

- Strong applicability, suitable for direct drive / computer sewing machine as 373, 438, 1373, 1903.
- Easy to install, just need to connect 2 cables to start working, with up and down adjustment function.
- Greater functionality: four-hole, two-hole and three-hole non-standard buttons, sewing range 8~28mm, special customized machine sewing range up to 5~35mm.
- The button clamp is directly controlled by the imported cylinder, the reaction is sensitive, and the size is adjustable, suitable for different types of buttons.
- The vibrating plate is stamped and formed by special materials. It has strong vibration transmission capability, accurate identification of the front and back of the button, and has a start-stop function. Adopt induction protection device, the light is on when the buckle is closed, and the light is off when the buckle is opened sewing protection function, longer service life and more power saving.
- Cylinder drive type, sensitive, easy to adjust, 15% more efficient than traditional models.
- Each machine comes standard with 14 kinds of button positioning claw mounting plates, which can be replaced according to different buttons, and only need two screws for easy replacement.
- Using a 7-inch capacitive display, can display Chinese, English, Vietnamese three languages. Faster response and smooth operation.
- 适用能力强, 适配直驱/电脑373, 438, 1373, 1903。
- 安装方便只需2根连接线就可以使用, 设有上下调节功能。
- 功能强大: 四孔, 二孔以及三孔等非标准的纽扣, 缝制范围8~28mm, 特殊定制的机器缝制范围可达5~35mm。
- 扣夹采用进口气缸直接控制, 反应灵敏, 且大小可调, 适用不同类型的纽扣。
- 振动盘采用特殊材料一次性冲压成型, 震动传导能力强, 纽扣正反面识别准确, 设有起停功能, 缝制保护功能, 采取感应保护装置, 扣夹闭合时灯亮起, 扣夹张开时灯熄灭使用寿命更长, 更加省电。
- 采用气缸传动式, 反应灵敏, 调节方便, 比传统机型的效率提高了15%。
- 每台机器标配14种纽扣定位爪安装板, 可根据不同的纽扣进行更换, 且只需两个螺丝, 更换方便。
- 采用7英寸的电容显示屏, 可显示中文, 英文, 越南文三种语言。反应更快, 操作流畅。

Contact